



RIG TWO

CANTILEVER TRIPLE 1000HP



DRAWWORKS SUPERIOR 700E MODIFIED

Engine: GE 752

MAST OCD MODEL 550

Height: 142' **Max. Hook load:** 244,650 daN

SUBSTRUCTURE OCD MODEL 550

Max setback: 177,930 daN

Rotary/KB Beam to Ground: 5.63m/CH 4.97m

PUMPS F-1000'S

Engine: 2- Cat C-27 , 1050 HP

Liners Available: Different sizes upon request

MUD SYSTEM TWIN TANKS, 140M3

Shakers: 2 DFTS dual deck Linear shakers

Trip Tank: 3 m3

Suction Tank: 35 m3

Settling Tank 2: 30 m3

Agitators: 4 SOS Euro drive

Pumps: 2- 6x5x11 Mission Magnum

Pill tank: 5 m3

Settling Tank 1: 35 m3

Shaker Tank: 30 m3

GEN SETS 2 STEWART AND STEVENSON 475KW

Engine: 2- Cummins QFX15,675 HP

Panel: MCC, Allen Bradley PLC

WELL CONTROL WAGNER FIVE STATION 90 GALLON

Annular: Shaffer 11" 5K

Pipe Rams: Shaffer 11" 5K

Manifold: 31/8" 5k

HCR: Cammeron HCR

TUBULARS

Collars: 18-165mm 4.5" DC

Drill Pipe: 340- 114mm 4.5" XH E

HWDP: 12 DC, 165mm 4.5" X,H

OVERHEAD

Top Drive: Tesco 250 Ton HMI, 475 HP

Hook/Block:

Drilling Line: 28.6 mm

MISCELLANEOUS

Water Tank: Self raising Dog House, 55 m3

Fuel Tank: TC-44 spec tank, 25,000l

Boiler: Cleaver Brooks 80 HP

Features: Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP handling system, rig leveling rams.

RIG LOADS

Rig: 26

Boiler:

Loader Wellsite Shack & Misc:

HZ DEPTH CAPABILITY 5000+ M