

RIG THREE

CANTILEVER TRIPLE ELECTRIC 1000HP



DRAWWORKS SUPERIOR 750 UE

Engine: Toshiba 1000 Amp DC

MAST DRECO 550

Height: 131' **Max. Hook load:** 180,000 daN 10 Lines

SUBSTRUCTURE DRECO SELF RAISING

Max setback: 140,000 daN

Rotary/KB Beam to Ground: 5.48 m/ CH 4.89m

PUMPS (2) F-1600

Engine: (2) each, GE 752, 1000 Amp

Liners Available: Different sizes upon request

MUD SYSTEM (2) 140 M3 USABLE FLUID

Shakers: Derrick Flow Line

Trip Tank: 3 m3

Suction Tank: 30 m3

Settling Tank 2: 30 m3

Agitators: 3- SOS Euro Drive

Pumps: 2 Mission Magnum 6x5x11

Pill tank: 7 m3

Settling Tank 1: 30 m3

Shaker Tank: 30 m3

GEN SETS (2) KATO 1225 KW, (1) 800 KW

Engine: (2) Cat 3512's, (1) Cat C-27 **Panel:** CPS, Four bay SCR, Allen Bradely PLC

WELL CONTROL KOOMEYSIX STATION 245 GALLON

Annular: 11" 5M Shaffer

Pipe Rams: 11" 5M Shafco

Manifold: 3 1/8" 35,000KPA

HCR: Cammeron HCR

TUBULARS

Collars: 18- 165mm 4.5" XH

HWDP: 60-101.6mm 4" FH

Drill Pipe: 415- 101.6mm 4" FH X-95

OVERHEAD

Top Drive: JH Electric, 350 Ton, AC Drive **Hook/Block:** Gardner Denver 250 Ton

Drilling Line: 28.6 mm

MISCELLANEOUS

Water Tank: 55 m3

Fuel Tank: TC-44 fuel tank, 30,000l storage

Boiler: 125 HP Volcano

Features: Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP Lifting System, Baylor Brake, Self Elevating Sub.

RIG LOADS

Rig: 36

Boiler:

Loader Wellsite Shack & Misc:

HZ DEPTH CAPABILITY 5000+ M

