



RIG FOUR

CANTILEVER DOUBLE 500HP



DRAWWORKS NATIONAL 370

Engine: Cat 3406E 575 HP

MAST DERRICK MANUFACTURING

Height: 97' **Max. Hook load:** 148,000 daN

SUBSTRUCTURE EDMONTON FABRICATORS LTD

Max setback: 115,000 daN

Rotary/KB Beam to Ground: 5.02m/ CH 4.26m

PUMPS (2) F-800

Engine: Detroit 60 Series

Liners Available: Different sizes upon request

MUD SYSTEM (1) TANK 77M3

Shakers: DFTS Linear Motion

Trip Tank: 3 m3

Suction Tank: 18.5 m3

Settling Tank 2:

Agitators: SOS Euro Drive

Pumps: 6x5x11 Mission Magnum

Pill tank: 4 m3

Settling Tank 1: 18.5 m3

Shaker Tank: 24.1 m3

GEN SETS (2) STANFORD 300 KW GENERATOR

Engine: Cummins NTA 855G

Panel: MCC

WELL CONTROL KOOMEY FIVE STATION 80 GALLON

Annular: 228.6mm Townsend TL90 3M

Pipe Rams: 228.6mm Townsend LWP 3M

Manifold: 3 1/8" 3M

HCR: MCm 3M

TUBULARS

Collars: 18-165mm 4.5" XH

HWDP: 60- 101.6mm 4" FH

Drill Pipe: 200- 101.6mm 4" FH X-95

OVERHEAD

Top Drive: TSM 150 Ton Swivel

Hook/Block: High Quality 150 Ton 4X 30" Sheaves

Drilling Line: 28.6 mm

MISCELLANEOUS

Water Tank: 63m3

Fuel Tank: 28,000 Liters

Boiler: 80 HP Lister

Features: Hydraulic Skate Catwalk, BOP lifting System, Rig Smart Crown Saver Pipe Tubs.

RIG LOADS

Rig: 24

Boiler:

Loader Wellsite Shack & Misc:

HZ DEPTH CAPABILITY 3600+ M