



RIG FIVE

CANTILEVER TRIPLE 750HP



DRAWWORKS BREWSTER N-45 MODIFIED

Engine: (2) Detroit 60 Series 475 HP

MAST DRECO 510

Height: 133' **Max. Hook load:** 157,460 daN 10 Lines

SUBSTRUCTURE EDMONTON FABRICATORS LTD

Max setback: 115,000 daN

Rotary/KB Beam to Ground: 5.02m/ CH 4.26m

PUMPS (2) F-1000

Engine: (2) Cat C-27

Liners Available: Different sizes upon request

MUD SYSTEM (2) TANK, 110 M3 USABLE FLUID

Shakers: (2) Swaco Liner Motion **Pumps:** 2 Mission Magnum 6x5x11

Trip Tank: 3 m3

Pill tank: 4 m3

Suction Tank: 25 m3

Settling Tank 1: 25 m3

Settling Tank 2: 30 m3

Shaker Tank: 30 m3

Agitators: 3- SOS Euro Drive

GEN SETS (2) STANFORD 350 KW

Engine: (2) Detroit 60 Series 625HP

Panel: MCC

WELL CONTROL KOOMEY SIX STATION 90 GALLON

Annular: 11" 3M Shaffer

Pipe Rams: 11" 3M Shafco

Manifold: 3 1/8" 35,000KPA

HCR: Cammeron HCR

TUBULARS

Collars: 18- 165mm 4.5" XH

Drill Pipe: 300- 101.6mm 4" FH X-95

HWDP:

OVERHEAD

Top Drive: JH Electric 250 Ton, AC

Hook/Block: Gardner Denver 250 Ton

Drilling Line: 28.6 mm

MISCELLANEOUS

Water Tank: 63m3

Fuel Tank: 20,000L Storage

Boiler: 80 HP Napanee

Features: Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP Lifting System.

RIG LOADS

Rig: 24

Boiler:

Loader Wellsite Shack & Misc:

HZ DEPTH CAPABILITY 4000+ M