



RIG SIX

TELI-DOUBLE 500 HP



DRAWWORKS SPENCER HARRIS 600, MODIFIED

Engine: Cummins QSM, 410HP

MAST SPENCER HARRIS

Height: 97' **Max. Hook load:** 112,225 daN 8 Lines

SUBSTRUCTURE SPENCER HARRIS, STEP DOWN

Max setback: 89,000 daN

Rotary/KB Beam to Ground: 3.60 m/ CH 3.35m

PUMPS F-800

Engine: (2) Detroit 60 Series 475 HP

Liners Available: Different sizes upon request

MUD SYSTEM SINGLE TANK 51 M3

Shakers: (1)DFTS 275 XG Dual Deck Linear

Pumps: 2 Mission Magnum 6x5x11

Trip Tank: 3 m³

Pill tank: 4 m³

Suction Tank: 14.6 m³

Settling Tank 1: 14.6 m³

Settling Tank 2: m³

Shaker Tank: 14.6 m³

Agitators: 2- SOS Euro Drive

GEN SETS (1) CUMMINS POWER 265 KW

Engine: Cummins QSM 11 350 HP

Panel: MCC

WELL CONTROL WAGNER FIVE STATION 80 GALLON

Annular: 228.6mm Townsend TL90 3M

Pipe Rams: 228.6mm Townsend LWP 3M

Manifold: 3 1/8" 3M

HCR: MCM 3M

TUBULARS

Collars: 10- 165mm 4.5" XH

Drill Pipe: 200- 101.6mm 4" FH X-95

HWDP: 60-101.6mm 4" FH

OVERHEAD

Top Drive: TSM 150 Ton Swivel

Hook/Block: McKissick 100 Ton

Drilling Line: 25.4 mm

MISCELLANEOUS

Water Tank: 60 m³

Fuel Tank: 15,000l storage

Boiler: 100 HP Hurst

Features: Rig Smart Crown Saver, pipe tubs.

RIG LOADS

Rig: 12

Boiler:

Loader Wellsite Shack & Misc:

HZ DEPTH CAPABILITY 2400+ M